FABRITEX
PERFORMANCE FLEXIBLE COMPOSITES

513 BRYANT RD.
CONROE, TEXAS 77303
TEL. 281-821-2400 / 936-494-4300

DATA SHEET FAB-432-BA

PRODUCT INFORMATION

PRODUCT NAME	**FAB-432-BA**
PRODUCT DESCRIPTION	**CROWFOOT SATIN WEAVE FIBERGLASS FABRIC COATED WITH BLACK PIGMENTED ACRYLIC FOR WELDING CURTAINS**

PRODUCT SPECIFICATIONS

SUBSTRATE TYPE	**FIBERGLASS/CROWFOOT SATIN WEAVE FABRIC**	
COATING MEDIUM	**ACRYLIC**	
COLOR	**BLACK**	
WIDTH	**60 (INCHES)**	
		METHOD
WEIGHT	**14.0 ± 5% (OUNCES/SQ. YARD)**	**ASTM-D-3776**
OVERALL THICKNESS (NOMINAL)	**0.015 ± 0.001 (INCHES)**	**ASTM-D-1777**
TENSIL STRENGTH WARP	**350 (POUNDS/SQUARE INCH)**	**ASTM-D-5034**
TENSIL STRENGTH FILL	**300 (POUNDS/SQUARE INCH)**	**ASTM-D-5034**
TEAR STRENGTH WARP	**50 (POUNDS)**	**ASTM-D-5587**
TEAR STRENGTH FILL	**50 (POUNDS)**	**ASTM-D-5587**
BURST STRENGTH	**600 PSI**	**ASTM-D-3786**
FLAME RESISTANCE	**CHAR LENGTH 1" MAX AFTERGLOW 1 SECOND MAX FLAME OUT 1 SECOND MAX**	**ASTM-D-6413**
TEMPERATURE RESISTANCE	**CONTINUOUS INTERMITTENT**	**1000^0F 1100^0F**

The data in this Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. To the best of our knowledge, the information contained herein is accurate. However, Fabritex assumes no liability whatsoever for the accuracy or completeness of the information contained in this Data Sheet. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution.