FABRITEX
PERFORMANCE FLEXIBLE COMPOSITES

513 BRYANT RD.
CONROE, TEXAS 77303
TEL. 281-821-2400 /936-494-4300

DATA SHEET FBX-05L-ACR

PRODUCT SPECIFICATIONS

SUBSTRATE TYPE	**WOVEN FIBERGLASS (“E” TYPE)**	
OVERALL THICKNESS	**0.00685**	**INCHES**
BACKING THICKNESS	**0.00485**	**INCHES**
ADHESIVE THICKNESS	**0.00200**	**INCHES**
ADHESIVE TYPE	**ACRYLIC**	
OPERATING TEMPERATURE	**-40°F TO 350°F**	**-40°C TO +177°C**
PEEL/TACK	**3.5-4.5**	**LB/IN**
TENSILE STRENGTH	**125/110 (W/F)**	**LB/IN**
TEAR RESISTANCE	**3/3 (W/F)**	**LB**
ADHESIVE SHELF LIFE	**12**	**MONTHS**

The data in this Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. To the best of our knowledge, the information contained herein is accurate. However, Fabritex assumes no liability whatsoever for the accuracy or completeness of the information contained in this Data Sheet. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution.