FABRITEX
PERFORMANCE FLEXIBLE COMPOSITES

513 BRYANT RD.
CONROE, TEXAS 77303
TEL. 281-821-2400 / 936-494-4300

DATA SHEET GLASS 2025-9383 A

PRODUCT INFORMATION

PRODUCT NAME	**TREATED FIBERGLASS**
PRODUCT DESCRIPTION	**GLASS 2025-9383 A IS A SPECIALIZED PLAIN WEAVE FIBERGLASS FABRIC, ASBESTOS FREE FEATURING A LIGHT COATING OF 2% ACRYLIC SPECIFICALLY DESIGNED FOR FABRIC STABILIZATION AND RAVELING REDUCTION**

PRODUCT SPECIFICATIONS

SUBSTRATE TYPE	**NON ABESTOS PLAIN WEAVE FIBERGLASS FABRIC**	
COATING MEDIUM	**FINISHED WITH TREATMENT 9383**	
WIDTH	**60 (INCHES)**	
		METHOD
WEIGHT	**18 ± 5% (OUNCES/SQ. YARD)**	**ASTM-D-3776**
OVERALL THICKNESS (NOMINAL)	**0.03 ± 5% (INCHES)**	**ASTM-D-1777**
TENSIL STRENGTH WARP	**250 (POUNDS/SQUARE INCH)**	**ASTM-D-5034**
TENSIL STRENGTH FILL	**200 (POUNDS/SQUARE INCH)**	**ASTM-D-5034**
FLAME RESISTANCE	**CHAR LENGTH 1" MAX AFTERGLOW 1 SECOND MAX FLAME OUT 1 SECOND MAX**	**ASTM-D-6413**
MAXIMUM TEMPERATURE	**+ 1000 ^{0} F**	**ASTM-D-3775**

The data in this Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. To the best of our knowledge, the information contained herein is accurate. However, Fabritex assumes no liability whatsoever for the accuracy or completeness of the information contained in this Data Sheet. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution.