FABRITEX
PERFORMANCE FLEXIBLE COMPOSITES

513 BRYANT RD.
CONROE, TEXAS 77303
TEL. 281-821-2400 / 936-494-4300

DATA SHEET — HOOK/LOOP FRT

PRODUCT SPECIFICATIONS

PRODUCT DESCRIPTION	**FIRE RETARDANT HOOK & LOOP FASTENING TAPE**	
MATERIAL	**100% POLYAMIDE (NYLON)**	
COLOR	**GRAY**	
CONSTRUCTION	**WOVEN**	
THICKNESS (HOOK/LOOP)	**≥ 0.075 INCH**	**≥ 1.90 MM**
WEIGHT	**≥ 0.20 G/INCH^2 (HOOK)** **≥ 0.23 G/INCH^2 (LOOP)**	**≥ 0.031 G/CM^2 (HOOK)** **≥ 0.036 G/CM^2 (LOOP)**
HOOK/LOOP NUMBER	**≥ 300 INCH^2 (HOOK)**	**≥ 640 INCH^2 (LOOP)**
MELTING POINT OF NYLON	**210^{0}C**	
SOFTENING POINT OF NYLON	**160^{0}C**	
UV RESISTENCE	**POLYAMIDE DOES NOT HAVE A GOOD RESISTANCE TO SUNLIGHT**	
BACK COATING	**POLYURETHANE RESIN**	
RESISTANCE TO TEMPERATURES	**-20^{0}C +120^{0}C**	**-4^{0}F + 248^{0}F**

The data in this Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. To the best of our knowledge, the information contained herein is accurate. However, Fabritex assumes no liability whatsoever for the accuracy or completeness of the information contained in this Data Sheet. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution.