FABRITEX
PERFORMANCE FLEXIBLE COMPOSITES

513 BRYANT RD.
CONROE, TEXAS 77303
TEL. 281-821-2400 / 936-494-4300

DATA SHEET S/S D-RING

PRODUCT INFORMATION

PRODUCT NAME	**S/S D-RING 10GA**
PRODUCT SPECIFICATIONS	**STAINLESS STEEL D RINGS WITH A WELDED JOINT, PRIMARILY USED WITH WEBBING TO CINCH DOWN AND SECURE REMOVABLE INSULATION BLANKETS. IDEALLY USED AS BUCKLES WITH STRAPS WHICH HOLD THE INSULATION BLANKETS IN PLACE. FABRITEX IS ABLE TO SUPPLY D RINGS OR RETANGULAR RINGS PER CUSTOMER SIZE, THE MATERIAL IS AVAILABLE IN MILD STEEL IN NICKEL PLATED OR STAINLESS STEEL.**

TYPICAL PROPERTIES

MATERIAL	**STAINLESS STEEL, GALVANIZED**
WIRE DIAMETER	**3MM, 3.4MM, 4MM**
SURFACE	**POLISHING AND BRIGHT**
DIAMETER	**25MM, 30MM, 38MM, 50MM**
APPLICATION	**REMOVABLE INSULATION BLANKETS OR JACKETS**

1. 25 X 22 X 3.4MM	**(1” X 7/8” X 10 GA)**
2. 38 X 32 X 3.4MM	**(1-1/2” X 1-1/4” X 10 GA)**
3. 30 X 27 X 3MM	**(1-3/16” X 1-1/8” X 11 GA)**
4. 30 X 25 X 3MM	**(1/3/16” X 1 X 11 GA)**
5. 30 X 22 X 3MM	**(1-3/16” X 7/8” X 11 GA)**
6. 50 X 42 X 3.4MM	**(2” X 1-5/8” X 10 GA)**
7. 25 X 22 X 4MM	**(1” X 7/8” X 4 MM)**

The data in this Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. To the best of our knowledge, the information contained herein is accurate. However, Fabritex assumes no liability whatsoever for the accuracy or completeness of the information contained in this Data Sheet. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution.