FABRITEX
PERFORMANCE FLEXIBLE COMPOSITES

513 BRYANT RD.
CONROE, TEXAS 77303
TEL. 281-821-2400 / 936-494-4300

DATA SHEET TT-3SS

PRODUCT INFORMATION

PRODUCT NAME	**ARAMID SEWING THREAD**
PRODUCT SPECIFICATIONS	**ARAMID SEWING THREAD THAT HAVE EXTEMELY HIGH STRENGTH, EXCELLENT HEAT RESISTANCE AND FLAME RETARDANT PROPERTIES. DOES NOT CATCH FIRE, MELT OR DROP, SO IT IS AN EXCELLENT CHOICE FOR FLAME-RETARDANT APPLICATIONS SUCH AS: SEWING FIREFIGHTER UNIFORM, ANTI-CUTTING GLOVES, INSULATION COVERS.**

TYPICAL PROPERTIES

COLOR	**YELLOW**	
COATING TYPE	**PTFE**	
FIBER COUNT	**1000D**	
REINFORCEMENT	**3 PLYS S.S. 316L WIRE**	
DIAMETER	**0.3MM**	**0.012”**
TENSILE STRENGTH	**≥61.5N**	
ELONGATION	**6% -11%**	
MAX WORKING TEMPERATURE	**50 ^{0}C TO 350^{0}C** **316L S.S. WIRE 1000^{0}C**	**-58 ^{0}F TO 662^{0}F** **1832^{0}F**

The data in this Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. To the best of our knowledge, the information contained herein is accurate. However, Fabritex assumes no liability whatsoever for the accuracy or completeness of the information contained in this Data Sheet. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution.