FABRITEX
PERFORMANCE FLEXIBLE COMPOSITES

513 BRYANT RD.
CONROE, TEXAS 77303
TEL. 281-821-2400 / 936-494-4300

DATA SHEET VERMICULITE

PRODUCT INFORMATION

PRODUCT NAME	**TREATED FIBERGLASS FABRIC**
PRODUCT DESCRIPTION	**FABRITEX 18OZ IS ASBESTOS FREE AND HAVE BEEN SPECIALLY MANUFACTURED AND COATED WITH VERMICULITE TO PROVIDE A HIGHER TEMPERATURE RESISTANCE IN CERTAIN APPLICATIONS. THIS FABRIC WORKS VERY WELL IN WELDING CURTAIN TYPE APPLICATIONS. IF THIS FABRIC IS USED FOR REMOVABLE INSULATION JACKETING AGAINST HOT SURFACES ABOVE 500^{0}F, STAINLESS STEEL BLANKET MESH IS RECOMMENDED DUE TO CONSIDERABLE LOSS IN TENSILE STRENGTH.**

PRODUCT SPECIFICATIONS

	18 OZ	
COLOR	**GOLD**	
WEIGHT	**18.0**	**(OZ/SQ YD)**
THICKNESS	**0.030”**	
WEAVE	**PLAIN**	
MAXIMUM TEMPERATURE	**1500 ^{0}F**	
MAXIMUM TEMPERAURE	**1100 ^{0}F**	**CONTINUOUS**
WIDTH	**60”**	

The data in this Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. To the best of our knowledge, the information contained herein is accurate. However, Fabritex assumes no liability whatsoever for the accuracy or completeness of the information contained in this Data Sheet. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution.